




412EIA-CE-002

4-1/2" EIA Coupling Element



Radio Frequency Systems line of high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to CELLFLEX® and HELIFLEX® coaxial cables. RFS connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in a variety of mating interfaces. To join two cables with IEC connectors, two identical socket connectors are installed on either end of the cables to be joined, and a coupling element is used to make the connection of the center conductor. The coupling element must be ordered separately with the exception of the S-Line male versions that have a captivated coupling element. Connectors are available in sizes matching the nominal cable size. EIA connectors provide optimal power handling for the complete transmission line system. The coupling element comes along with the necessary hardware (O-ring and nuts and bolts) to connect the IEC connectors.

Features / Benefits

- Excellent gas tightness, Overpressure for increased voltage handling is maintained throughout the system
- Robust Mechanical Design, Superior and consistent performance guarantees outstanding system characteristics.
- Extremely low reflection factor, Outstanding low reflection factor improves overall system performance and margin and reduces mismatch losses
- Totally Waterproof according to IP 68, Assures safe, long term operation in the harshest of environments. System tightness doesn't have to rely on overpressure from dehydration equipment.
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical Features

STRUCTURE

Cable Type	Air Dielectric
Connector Interface Size	4-1/2" EIA

MECHANICAL SPECIFICATIONS

Connector Length	77mm (3.03in)
Connector Outer Diameter	105mm (4.13in)
Inner Conductor Material / Coating	Copper Alloy / Silver
Outer Conductor Material / Coating	Copper Alloy / Silver
Sealing Method	O-ring

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 Ω
-------------------	------