

**43MR-LCF12-ECO**

4.3-10 Male Right Angle Connector for 1/2" Coaxial Cable, ECO-Series



ECO Series connectors are designed for use with CELLFLEX® ECO cables.

Features / Benefits

- Cost effective two-piece design for safe and easy installation
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 67 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical Features**STRUCTURE**

Cable Type	LCF
Cable Size	1/2"
Qualified Cable Types	LCF12-50J / JFN-ECO
Model Series	ECO Standard Series
Connector Interface Size	4.3-10
Connector Interface Gender	Male

MECHANICAL SPECIFICATIONS

Connector Length	59mm (2.323in)
Connector Outer Diameter	32.2mm (1.268in)
Inner Conductor Material / Coating	Brass Alloy / Silver Plated
Outer Conductor Material / Coating	Brass Alloy / Trimetal
Insulation Material	PTFE
Sealing Method	O-Ring

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 Ω	
Connector Frequency Range	DC - 6.0 GHz GHz	
PIM ratio Typical (2 x 20 W Carrier)	-155 dBc	
Frequency Range	VSWR	Return Loss
690 < f ≤ 960MHz	1.1	26.4
1700 < f ≤ 2700MHz	1.13	24.3
2700 < f ≤ 3000MHz	1.15	23.1

TESTING AND ENVIRONMENTAL

Ingress Protection (IP) Rating	IP67
--------------------------------	------



43MR-LCF12-ECO

4.3-10 Male Right Angle Connector for 1/2" Coaxial Cable, ECO-Series

ACCESSORIES

Wrench Size Connector Interface	22mm (0.866in)
Wrench Size Connector Front Part	17mm (0.669in)
Wrench Size Connector Rear Part	20mm (0.787in)
Trimming Tool	TRIM-SET-L12-C02



Related Documents



Installation Instruction **-LCF12-ECO
Installation Instructions