

**716M-LCF12-C03**

7-16 DIN Male Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

rfs 716m-lcf12-
c03.png

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.

Features / Benefits

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical Features**STRUCTURE**

Cable Type	LCF	
Cable Size	1/2"	
Qualified Cable Types	LCF12-50J / JFN	LCF12-50J / JFN-ECO
Model Series	C03 Standard Series	
Connector Interface Size	7/16	
Connector Interface Gender	Male	

MECHANICAL SPECIFICATIONS

Connector Length	52.8mm (2.08in)
Connector Outer Diameter	36mm (1.42in)
Inner Conductor Material / Coating	Brass Alloy / Silver Plated
Outer Conductor Material / Coating	Brass Alloy / Trimetal Plated
Insulation Material	TPX / PTFE
Sealing Method	O-Ring



716M-LCF12-C03

7-16 DIN Male Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 Ω	
Connector Frequency Range	DC - 6.0 GHz GHz	
PIM Ratio (2 x 20 W Carrier)	-157 dBc	
PIM ratio Typical (2 x 20 W Carrier)	-160 dBc	
Frequency Range	VSWR	Return Loss
0 < f ≤ 1.0 GHz	1.03	36.6
1.0 < f ≤ 2.7 GHz	1.04	34.1
2.7 < f ≤ 3.7 GHz	1.08	28.3
3.7 < f ≤ 5.0 GHz	1.15	23.1
5.0 < f ≤ 6.0 GHz	1.25	19.1

TESTING AND ENVIRONMENTAL

Ingress Protection (IP) Rating	IP68
--------------------------------	------

ACCESSORIES

Wrench Size Connector Interface	32mm (1.26in)
Wrench Size Connector Front Part	20mm (13/16in)
Wrench Size Connector Rear Part	20mm (13/16in)
Trimming Tool	TRIM-SET-L12-C02



Related Documents

 **Application Note**
External Datasheet

 **Installation instruction **-LCF12-C03**
Installation Instructions