




7F7FB-HYB90-02

Hybrid Quarter Wave Surge Arrestor 7-16 DIN female - female bulkhead, 698 to 2700 MHz



This 7-16 DIN style hybrid quarter wave surge arrestor with gas capsule for high-power and low IM application is foreseen for bulkhead mounting or in-line arrangement with grounding wire connection (not included) via M8 thread.

Surge arrestors are designed to protect wireless base stations, switching centers and transmission line from the damaging effects of extreme high voltage surges caused by lightning strikes. Lightning strikes, even on grounded systems, can implant crushing voltages on RF transmission lines, creating voltage spikes on the center conductor of coaxial cable and putting the network out of commission. These RFS lightning protection devices are designed and tested to the most demanding specifications. They are rated to protect against both direct and indirect multiple strikes in the harshest environments imaginable. Their rugged construction utilizes solid metal housings, spring bronze contacts and superior plating, which results in outstanding system protection and operating continuity.

Features / Benefits

- Allows 2.176MHz signal to pass for AISG systems
- Broadband operation - DC and RF (698-2700 MHz)
- DC continuity on center conductor for reliable operation (DC pass)
- Multiple strike protection provides current handling capability of 20 kA
- Replaceable gas capsules for easy maintenance
- Outstanding VSWR and IM performance
- Water resistant to IP67 standards (mated)
- Reverse installation possible without performance impact

Technical Features

STRUCTURE

Product Line	Coaxial Cable Components
Product Type	Surge Arrestor
Surge Arrestor Type	Hybrid Quarter Wave
Design	90° Stub
Coaxial Cable Type	Foam Dielectric, Ultraflexible Foam Dielectric, Radiating Cable
Connector Interface	7-16 DIN



7F7FB-HYB90-02

Hybrid Quarter Wave Surge Arrestor 7-16 DIN female - female bulkhead, 698 to 2700 MHz

MECHANICAL SPECIFICATIONS

Configuration	Bulkhead
Connector A	7-16 DIN Female
Center Contact Connector A	Brass, silver plated
Outer Contact Connector A	Brass, Tri metal
Connector B	7-16 DIN Female
Center Contact Connector B	Brass, silver plated
Outer Contact Connector B	Brass, Tri metal
Body	Brass, Tri metal
Dielectric	PTFE
Gasket	Silicone rubber
Mounting / Grounding	Bulkhead; Thread for grounding M8

ELECTRICAL SPECIFICATIONS

Frequency Range - MHz	698 - 2700
VSWR	698 - 725 MHz: 1.25 (19.1) 725 - 800 MHz: 1.20 (20.8) 800 - 2675 MHz: 1.18 (21.7) 2675 - 2700 MHz: 1.25 (19.1)
Insertion Loss	0.10
3rd Order IM Product @ 2x20 Watts	-160 dBc
Power handling	2.7 kW@698, 1.3 kW@2700 (at 20°C, sea level, VSWR 1.0)
Surge current handling capability	20 kA, 8/20 μs
Residual pulse	<350μJ (test puls 4kV 1.2/50μs)

TEMPERATURE SPECIFICATIONS

Operation Temperature	-45 to 85 (-49 to 185)
-----------------------	------------------------

PACKAGING INFORMATION

Package Quantity	1
------------------	---

External Document Links	Notes
-------------------------	-------