

**BD150*W Dehydrator Series**

BD1502W Automatic Dehydrator, 208-253 VAC 50/60Hz



The dehydrator removes the moisture from damp ambient air to deliver a reliable, constant, on demand source of dry and pressurised air, which is critical to prevent the systems from performance and reliability degradation by condensation. The BD1500W series dehydrators offer pressurization solutions to transmission lines and antennas in both telecom and broadcasting applications. Its low pressure models (suffix LP) are suitable for applications where reduced pressure is required, for example, pressurisation of broadcast antenna radomes, microwave waveguides and other transmission lines. The inherent reliability of the BD series design, combined with the high output capacity and remote real-time data capabilities make these units an ideal choice for pressurisation of systems at unattended sites. The BD1500W Series dehydrators employ a fully digital operating platform offering the most accurate readings of operating variables, either from the front panel or by a remote IP connection.

Features / Benefits

- Air Delivery up to 1770L/h
- Operating pressure can be changed by a simple adjustment at the dehydrator
- Available in 220VAC Power Supply • Remote Real-Time Data and Alarm Reset Capabilities
- SNMP Communication Compatible
- Digital Display of All Operating Parameters
- Imperial and Metric Unit of Measure Options
- 8,000 Hour Maintenance Interval
- Compact and Lightweight
- Versatile Installation, Standalone, Optional Rack/Wall Mount
- Ultra Quiet Compressor

Technical Features**GENERAL SPECIFICATIONS**

Product Type	Automatic Dehydrator
Model	BD1502W
max. System Volume @Sea Level	14,863 l
Output Capacity	Normal: 1416 Continuous; Maximum: 1770 Emergency
Output Pressure	13.8 - 103.4 (2 - 15)
Output Air Relative Humidity	>2 RH
Number of Outlets	1
Output Fitting	Single, 3/8" Press-to-Lock tube fitting
Noise Level at 3m	48
Network Management	via Web Browser or SNMP through RJ-45 Ethernet Connection

ELECTRICAL SPECIFICATIONS

Operating Voltage	208 - 253 VAC, 50 / 60Hz
Operating Current	3.5

**BD150*W Dehydrator Series**

BD1502W Automatic Dehydrator, 208-253 VAC 50/60Hz

MECHANICAL SPECIFICATIONS

Dimension H x D x W	68.6 x 30.8 x 43.8 cm
Weight	36.3 kg

ENVIRONMENTAL

Ambient Temperature Range	+5 to +30 Note: 2 °C
---------------------------	----------------------

ALARMS

Alarm	Standard Alarm - Complete readings of all critical measurement points, individual alarm indication display, including SNMP communication.
	High Outlet Pressure Alarm
	Low Outlet Pressure Alarm
	High Humidity Alarm
	High Flow Rate Alarm
	High Cabinet Temperature Alarm
	High Compressor Last Run Time Alarm

ACCESSORIES

Model Name	Description
P018302	6-Month Maintenance Kit for BD150*W* Series
P012252	8000 Hour Maintenance Kit for BD150*W* Series
P011674	Universal Rack Mounting Kit for BD150*W* Series
P011773	Wall Mounting Kit for BD150*W* Series
GLK-1	Start up Kit for Dehydrator
PWM2G	2-Port Manifold with Pressure Gauges
PWM2GC	2-Port Manifold with Pressure Gauges & Valves
MLK-2	Start up Kit for 2-Port Manifold
PWM4G	4-Port Manifold with Pressure Gauges
PWM4GC	4-Port Manifold with Pressure Gauges & Valves
MLK-4	Start up Kit for 4-Port Manifold
PWM8G	8-Port Manifold with Pressure Gauges
PWM8GC	8-Port Manifold with Pressure Gauges & Valves
MLK-8	Start up Kit for 8-Port Manifold
TUBE-38OD-PON	Gas inlet adaptor 1/8" NPT for 3/8" OD tube
TUBE-M12-G18	Gas inlet Adapter M12x1.5 - G1/8

*Screen image showing remote display of dehydrator status and alarms***NOTES**

Note 1: (15 Amp service recommended)

Note 2: Unit will go into SHUTDOWN mode if cabinet temperature exceeds 49°C



BD150*W Dehydrator Series

BD1502W Automatic Dehydrator, 208-253 VAC 50/60Hz

Related Documents



Dehydrator Sizing Reference Guide
Other Documents