



BREXXX
Micro Duct Reducer Connector



Micro Duct Reducer Connector are connecting two different sizes of Micro Modules.

Features / Benefits

- Connect two microducts which are different outer diameter
- Internal cone hole to prevent fiber hang up
- Easy installation, without any special tools
- Transparent plastics body, easy to observe the situation
- High temperature resistance -40°C 65°C
- Standard EN50411-2-8

Technical Features

ADDITIONAL INFORMATION

Column 1	Column 2	Column 3	Column 4	Column 5	Column 6
Model Name	Duct OD	Duct ID	Taper Hole	Pressure Resistance	
BRE5-3/2.1	5/3.5	3/2.1	3.5>2.1	25 bar	
BRE7-5/3.5	7/5.5	5/3.5	5.5>3.5	25 bar	
BRE8-5/3.5	8/6	5/3.5	6>6.5	25 bar	
BRE8-7/3.5	8/6	7/3.5	6>3.5	25 bar	
BRE10-5/3.5	10/8	5/3.5	8>3.5	25 bar	
BRE10-7/5.5	10/8	7/5.5	8>5.5	25 bar	
BRE10-8/6	10/8	8/6	8>6	25 bar	
BRE12-5/3.5	12/10	5/3.5	10>3.5	25 bar	
BRE12-7/3.5	12/10	7/3.5	10>3.5	25 bar	
BRE12-8/6	12/10	8/6	10>6	25 bar	
BRE12-10/8	12/10	10/8	10>8	25 bar	
BRE14-7/3.5	14/12	7/3.5	12>3.5	25 bar	
BRE14-10/8	14/12	10/8	12>8	25 bar	
BRE14-12/10	14/12	12/10	12>10	25 bar	
BRE16-10/8	16/13	10/8	13>8	25 bar	
BRE16-12/10	16/13	12/10	13>10	25 bar	
BRE16-14/10	16/13	14/10	13>10	25 bar	
BRE18-14/10	18/14	14/10	14>10	25 bar	