



CC-158-2

Clic clamp for RADIAFLEX® 1 5/8"



Clic Clamp, 1-5/8" RADIAFLEX polyamide black, halogen free  
Fire class UL94HB  
UL746C rated material suitable for outdoor applications

Features / Benefits

Safe and efficient installation of RADIAFLEX® cable with clic-clamps. Simple mounting by using wall plugs and screws. Simply push in by hand, clamp will grip and lock by applying slight pressure.

Technical Features

GENERAL SPECIFICATIONS

|              |                 |
|--------------|-----------------|
| Product Type | Hanger          |
| Hanger Type  | Clic clamp      |
| Cable Type   | Radiating Cable |
| Color        | Black           |

MECHANICAL SPECIFICATIONS

|                                  |           |
|----------------------------------|-----------|
| Cable Size                       | 1-5/8     |
| Number of Cable / Waveguide Runs | 1         |
| Material                         | Polyamide |

TESTING AND ENVIRONMENTAL

|                          |                                |
|--------------------------|--------------------------------|
| Fire Class               | UL94 HB                        |
| Installation Temperature | -20°C to 80°C (-4°F to 176°F)  |
| Operation Temperature    | -50°C to 85°C (-58°F to 185°F) |
| Storage Temperature      | -50°C to 85°C (-58°F to 185°F) |

