

**CDS10-43-694/3800**

10dB Directional Coupler

cdsx-43-698-2700-01_directionalcoupler_re

RFS CDS*-43 series Directional Coupler have been designed for a variety of wireless applications in the frequency band from 694 to 3800MHz. The unit couples off a defined fraction of a RF signal from 5 to 30 dB with minimal reflections or loss. The broad frequency range is ideally suited for multi-band distributed antenna systems or in combination with RADIAFLEX® radiating cables.

Features / Benefits

- 4.3-10-female interfaces
- PIM optimized design (160dBc @2x43dBm)
- Low insertion loss
- High power handling
- Small size, Low weight

Technical Features**STRUCTURE**

Product Type	Directional Coupler
Number of Input Ports	1
Number of Output Ports	2
Connector Type	4.3-10 female

ELECTRICAL SPECIFICATIONS

lower frequency	upper frequency
694	3800
Impedance	50 Ω
Insertion Loss max.	0.7 dB
Max. VSWR / Return Loss	1.3 (17.7)
Intermodulation (IM3)	-160dBc (2x43dBm)
Coupling Value	10 dB
Total Input Power	400 W

TEMPERATURE SPECIFICATIONS

Temperature Range	-25°C to 65°C (-13°F to 149°F)
-------------------	--------------------------------

MECHANICAL SPECIFICATIONS

Height	28.4mm (1.12in)
Width	69.2mm (2.72in)
Length	174.8mm (6.88in)

TESTING AND ENVIRONMENTAL

Environmental Class	IP65
---------------------	------

External Document Links

Notes