



CLAMP-158-S

Cable hanger, non-insulated, bolt-on, for 1 5/8" coaxial cable



Hanger, non-insulated, bolt-on for coaxial cable LCF158 and HCA158 and as fire resistance support for RCF158 and all RADIAFLEX® 1 5/8" with copper foil as outer conductor.
Made of stainless steel

Features / Benefits

- Stainless steel hangers for supporting coaxial cable to tower.
- Member mounting holes with up to M10 or 3/8"-16 hardware.
- Hanger may be attached to angle adapters, tower standoffs.
- Hanger may be attached to round member adapters through slot.
- Installation every 10m (30ft) as fire resistance support for RADIAFLEX®. Keep's the RADIAFLEX® cable in position during fire impact to prevent potential blocking of escape path. All installation components should be made of stainless steel.

Technical Features

GENERAL SPECIFICATIONS

Product Type	Hanger
Hanger Type	Bolt-On, non-insulated
Cable Type	Coaxial Foam Dielectric, Air Dielectric

MECHANICAL SPECIFICATIONS

Cable Size	1-5/8"
Number of Cable / Waveguide Runs	1
Material	Stainless Steel
Recommended / Maximum Clamp Spacing	0.8 / 1.2 (2.75 / 4)

TESTING AND ENVIRONMENTAL

Operation Temperature	-50°C to 85°C (-58°F to 185°F)
Storage Temperature	-50°C to 85°C (-58°F to 185°F)