




DBOF-0Z04SA-06-YC

Termination Module, 1 x in & 8 x drop ports, 9 x OneClick ports



Pre-connectorized optical distribution box as the most advanced FTTX network distribution node equipment, provide quick and reliable connection, good protection and management for the FTTX network

Features / Benefits

- Totally enclosed structure, the bottom shell and upper cover are welded by ultrasonic welding, which is non-detachable.
- Material: PP or PC+ABS.
- Moisture proof, waterproof, dust-proof, anti-aging.
- Protection level up to IP68.
- The interior is equipped with 1x2 FTB splitter,1x8 PLC splitter.
- Installation method: pole-mounted, aerial-mounted, wall-mounted hand hole, man hole etc. Note that PC+ABS materials are not suitable for use in underground environments.
- It can be equipped with drop cable storage tray to meet the storage of 30 meters 5mm round cable.

Technical Features

MECHANICAL SPECIFICATIONS

Material	PC+ABS
Dimensions (LxWxD)	171 x 179 x 66 (6.73 x 7.05 x 2.6)

TESTING AND ENVIRONMENTAL

Storage Temperature	-45°C to 75°C (-49°F to 167°F)
Operation Temperature	-40°C to 65°C (-40°F to 149°F)
Installation Temperature	-15°C to 40°C (5°F to 104°F)

ELECTRICAL SPECIFICATIONS

Protection Class	IP68
------------------	------

STANDARDS AND TESTING

Test Name	Standard	Specific Value
Color	Black	
Number of Pre-connectorized adaptors	9	
Splitter	1x8 PLC splitter	
Flammability	UL94-HB	
Neutral salt spray test (NSS)	48 h	