



GKIT-24-380P
Grounding Kit, Pre-formed Copper Strap, for E380



Standard Grounding Kit for Elliptical Waveguide E380
0.6m (24") grounding lead, 16mm² (7strand)
incl. screw kit M10 for grounding termination

Features / Benefits

The Premium Grounding Kit is designed to comply with RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) directives and has been verified by independent labs to withstand the damaging effects of lightning current. The pre-formed copper strap facilitates a proper attachment to the elliptical waveguide, insuring that the performance of the elliptical waveguide is not being compromised. The 16 mm² , 7 strand copper wire provides the most practical and effective low-inductance transfer of lightning induced current from your elliptical waveguide to your system ground.

Technical Features

STRUCTURE

Product Line	Elliptical Waveguide Accessories
Type of Grounding Kit	Pre-Formed Copper Strap
Cable Type	Elliptical Waveguide
Cable Size	E380
Sealing Kit	1x Roll butyl mastic 64 x 610mm (2.5" x 24") 1x Roll electrical tape 50mm x 6.1 m (2" x 20')
Material	Contact element: Copper with threaded studs, nuts and lock washers made of brass Cable Lug: Copper tin plated Grounding wire: Copper

MECHANICAL SPECIFICATIONS

Lug Attachment Method	Crimping, Crimp tool #6
Lug Style Size	1-hole Ø 10.1 mm crimp-on, tin-plated
Grounding Wire Length	0.61m (24in)
Grounding Wire Size	16 (7 strand)
Grounding Wire Color	Black
Grounding Body Color	Black
Sealing Class	IP68

TEMPERATURE SPECIFICATIONS

Operation Temperature	-50°C to 85°C (-58°F to 185°F)
Storage Temperature	-50°C to 85°C (-58°F to 185°F)

PACKAGING INFORMATION

Package Quantity	1
Weight per piece	0.6kg (1.4lb)

Related Documents



GKIT-24-380P

Grounding Kit, Pre-formed Copper Strap, for E380



Installation Instruction

Installation Instructions