



**HA-AD-SASA-40**  
Hybriflex Adapter, SC/APC Simplex



A high precision simplex SC/APC adapter with standard housing. Designed to provide low insertion loss, high return loss and excellent stability for RoF (Radio over Fibre) applications.

**Features / Benefits**

- Low insertion loss
- high strength
- high precision

**Technical Features**

**GENERAL SPECIFICATIONS**

|              |               |
|--------------|---------------|
| Product Type | Fiber Adaptor |
|--------------|---------------|

**ELECTRICAL SPECIFICATIONS**

|                     |        |
|---------------------|--------|
| Insertion Loss max  | 0.3 dB |
| Insertion Loss Typ. | 0.2 dB |

**MECHANICAL SPECIFICATIONS**

|                       |                  |
|-----------------------|------------------|
| Input Connector Type  | SC APC           |
| Output Connector Type | SC APC           |
| Height                | 9.3mm (0.366in)  |
| Width                 | 14.8mm (0.583in) |
| Length                | 27.4mm (1.079in) |
| Durability            | 1000 times       |

**TEMPERATURE SPECIFICATIONS**

|                       |                                                          |
|-----------------------|----------------------------------------------------------|
| Operating Temperature | -40°C to 70°C (-40°F to 158°F)                           |
| Environmental Class   | GR-326-core, IEC 61754, YD/T 1272 series, ROHS compliant |

