

**HA-FODC-LLBB-21-XX**

HYBRIFLEX™; Hybrid jumper cable, Single-mode fibre, 6 mm² Power cable, Box to Radio Module; with LC Duplex Connectors;

ha-fodc-llbb-21 new
version.jpg

RFS' HYBRIFLEX™ cabling solution for Remote Radio Head (RRH) combines optical fibre and DC power for RRHs in a single lightweight aluminum corrugated cable, making it the world's most innovative solution for RRH deployments. It was developed to reduce installation complexity and cost at cellular sites.

HYBRIFLEX™ cabling solutions allows mobile operators deploying RRH architecture to standardize RRH installation process and eliminates the need for and the cost of cable grounding.

The **HYBRIFLEX™** jumper is part of the cabling solution for RRH's. It consists of an armored part of length XX, a breakout part to the RRH and a breakout part to the distribution box. The breakout part to the RRH is outdoor ready and sealed according to IP68.

The jumper cables can be ordered in 1m - 20 m armored length in 1 m incremental.

Features / Benefits

- **Aluminum corrugated armor with outstanding bending characteristics** Minimizes installation time and enables mechanical protection and shielding
- **Built in animal protection** Improves the reliability of the installation
- **Outer conductor grounding** Eliminates typical grounding requirement and saves on installation costs
- **Lightweight solution and compact design** Decreases tower loads
- **Optical fibre and power cables housed in single corrugated cable** Saves CAPEX by standardizing RRH cable installation and reducing installation equipments
- **Outdoor polyethylene jacket** Ensure long-lasting cable protection

Technical Features

STRUCTURE

Cable Type	Hybrid jumper
------------	---------------

MECHANICAL SPECIFICATIONS

Outer Diameter Nominal	15.8mm (0.622in)
Cable Weight	0.235kg/m (0.158lb/ft)
Minimum Bending Radius	70mm (2.7in)
Minimum Bending Radius	125mm (5in)
Tensile Strength	150N (33.7lb)

**HA-FODC-LLBB-21-XX**HYBRIFLEX™; Hybrid jumper cable, Single-mode fibre, 6 mm² Power cable, Box to Radio Module; with LC Duplex Connectors;**DC POWER CABLE SPECIFICATIONS**

Number of DC Pairs	1
Maximum DC-Resistance Power Cable	3.3Ω/km (1.51Ω/kft)
Cross Section of Power Cable	6 ()
Shielding	Provided by Al armor
DC Wire Jacket Material	Polyethylene grey / blue (colours will change to comply with British Standards)
DC Wire Jacket Thickness	0.5mm (0.02in)
DC Cable Jacket	UV stable black PE
DC Standards (Meets or Exceeds)	IEC 60228
Current Rating	42 (ambient 35°C)
Power Termination End 1	Only barewire without ferrule
Power Termination End 2	With ferrule for box connection

CABLE JACKET

UV-Protection Individual and External Jacket	External Jacket: to IEC 60754-1/-2, Inner Jacket, DC conductors + Fibre cables EN 50289-4-17:2015
Jacket Material	UV stable black CPR class B2ca s1a d1 a1 + ISO 14001:2015 RoHS 2011/65/EU - China RoHS SJ/T 11364-2006 REACH (EC 1907/2006) UL1581 - UV Resistance Jacket

ARMOR SPECIFICATIONS

Armor Type	Corrugated aluminum
Maximum DC-Resistance of Armor	2.42Ω/km (0.74Ω/kft)
Copper Equivalent Cross Section of Armor	8.45 ()
Diameter Corrugated Armor	13.8mm (0.543in)

F/O CABLE SPECIFICATIONS

F/O Cable Type	Tight buffer, G657A2 Single-mode
Number of F/O Pairs	2
Core/Clad	9 /125
Secondary Protection Nominal	900µm (0.036in)
Loss (db)	Wavelength (nm)
0.4	1310
0.25	1550
Fiber Termination End 1	Duplex LC Connector
Fiber Termination End 2	Duplex LC Connector

TESTING AND ENVIRONMENTAL

Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Operation Temperature	-40°C to 85°C (-40°F to 185°F)
Installation Temperature	-20°C to 50°C (-4°F to 122°F)



HA-FODC-LLBB-21-XX

HYBRIFLEX™ ;Hybrid jumper cable, Single-mode fibre, 6 mm² Power cable, Box to Radio Module; with LC Duplex Connectors;

VARIATION INFORMATION

Model Number	HA-FODC-LLBB-21-01	HA-FODC-LLBB-21-02	HA-FODC-LLBB-21-03	HA-FODC-LLBB-21-04
Length	1m (3.281ft)	2m (6.562ft)	3m (9.843ft)	4m (13.123ft)
Model Number	HA-FODC-LLBB-21-05	HA-FODC-LLBB-21-06	HA-FODC-LLBB-21-07	HA-FODC-LLBB-21-08
Length	5m (16.404ft)	6m (19.685ft)	7m (22.966ft)	8m (26.247ft)
Model Number	HA-FODC-LLBB-21-09	HA-FODC-LLBB-21-10	HA-FODC-LLBB-21-15	HA-FODC-LLBB-21-20
Length	9m (29.528ft)	10m (32.808ft)	15m (49.213ft)	20m (65.617ft)

RECOMMENDED TOOLS

Earthing Kit	Hoisting Grip	Clamps
Earthing: GKSPEED20-12P	Boots for Nokia RRH: AOPC HA-AOPC-01	Boots for Ericsson RRH: IP-RC HA-FOPLUG-A-04
Clamps: single MBH-12S; double MBH-12D		