



HCA158-50J

1-5/8" HELIFLEX® Air-Dielectric Coaxial Cable



HELIFLEX® 1-5/8" low loss air dielectric cable

Features / Benefits

- **Low Attenuation**
The low attenuation of HELIFLEX® coaxial cable results in highly efficient signal transfer in your RF system.
- **Complete Shielding**
The solid outer conductor of HELIFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**
Special low VSWR versions of HELIFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**
HELIFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, HELIFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical Features

APPLICATIONS

Applications	Wireless Communication	TV & Radio	HF Defense	Mobile Radio	Cable Solutions
--------------	------------------------	------------	------------	--------------	-----------------

STRUCTURE

Cable Type	HCA
Size	1-5/8"
Jacket Option	Outdoor
Inner Conductor Material	Corrugated Copper Tube
Dielectric Material	Helical Polyethylene Spacer
Outer Conductor Material	Corrugated Copper
Jacket Material	Black Polyethylene

**HCA158-50J**

1-5/8" HELIFLEX® Air-Dielectric Coaxial Cable

MECHANICAL SPECIFICATIONS

Inner Conductor Diameter	18.6mm (0.73in)
Dielectric Diameter	39.8mm (1.56in)
Outer Conductor Diameter	46.6mm (1.83in)
Jacket Diameter	50.4mm (1.984in)
Cable Weight	1.3kg/m (0.89lb/ft)
Min Bending Radius, Single Bend	180mm (7in)
Min. Bending Radius, Repeated Bends	550mm (22in)
Bending Moment	42 Nm (31 lbf*ft)
Tensile Strength	1,500N (337lb)
Air Volume	1.4l/m (0.0151ft³/ft)
Recommended / Maximum Clamp Spacing	0.8 / 1.2 m (2.75 / 4) ft

ELECTRICAL SPECIFICATIONS

Impedance	50 +/- 0.5 Ω
Max. Operating Frequency	3 GHz
Velocity	95 %
Capacitance	70pF/m (21.3pF/ft)
Inductance	0.175μH/m (0.053μH/ft)
Peak Power Rating	270 kW
RF Peak Voltage	5,200 V
Jacket Spark	8,000 V RMS
DC-Resistance Inner Conductor	1.06Ω/km (0.33Ω/kft)
DC-Resistance Outer Conductor	0.39Ω/km (0.13Ω/kft)
Return Loss (VSWR) Performance	Standard
Min. Return Loss (Max. VSWR)	Typical 20.8dBdB (1.2 VSWR or better within the operation bands of most global frequency ranges. Premium also available. Contact factory for options in your specific frequency band.VSWR)

TESTING AND ENVIRONMENTAL

Fire Performance	Halogene Free
Compliance	RoHS 2011/65/EU China RoHS SJ/T 11364-2006 IEC 60754-1/-2 Halogen Acid Gases REACH (EC 1907/2006) IEC 60754-1/-2 Halogen Acid Gases
Phase Stabilized	Phase stabilized and phase matched cables and assemblies are available upon request.
Installation Temperature	-40°C to 60°C (-40°F to 140°F)
Storage Temperature	-70°C to 85°C (-94°F to 185°F)
Operation Temperature	-50°C to 85°C (-58°F to 185°F)

**HCA158-50J**

1-5/8" HELIFLEX® Air-Dielectric Coaxial Cable

ATTENUATION AND POWER RATING

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
0.5	0.044	0.013	270
1	0.062	0.019	196
1.5	0.076	0.023	160
2	0.088	0.027	138
10	0.197	0.06	61.4
20	0.279	0.085	43.4
30	0.342	0.104	35.4
50	0.444	0.135	27.3
88	0.592	0.18	20.5
100	0.632	0.193	19.2
108	0.657	0.2	18.4
150	0.778	0.237	15.6
174	0.84	0.256	14.4
200	0.902	0.275	13.5
300	1.11	0.339	11
400	1.29	0.394	9.44
450	1.38	0.419	8.83
500	1.45	0.443	8.41
512	1.47	0.449	8.3
600	1.6	0.488	7.64
700	1.74	0.529	7.03
800	1.86	0.568	6.59
824	1.89	0.577	6.49
894	1.98	0.603	6.2
900	1.98	0.605	6.2
925	2.01	0.614	6.11
960	2.05	0.626	6
1000	2.1	0.64	5.86
1250	2.37	0.722	5.21
1500	2.61	0.797	4.75
1700	2.8	0.853	4.44
1800	2.89	0.88	4.31
2000	3.06	0.932	4.08
2200	3.22	0.982	3.89
2300	3.3	1.01	3.81
3000	3.83	1.17	3.32
Note	Standard Conditions: For attenuation: VSWR 1.0, cable temperature 20°C (68°F). For average power: VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 115°C (239°F). No solar loading.		

External Document Links

Notes