



HCA78-50JFN

7/8" HELIFLEX® Air-Dielectric Coaxial Cable, flame retardant/ halogen free jacket



HELIFLEX® 7/8" low loss air dielectric cable

Features / Benefits

- Low Attenuation**
The low attenuation of HELIFLEX® coaxial cable results in highly efficient signal transfer in your RF system.
- Complete Shielding**
The solid outer conductor of HELIFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- Low VSWR**
Special low VSWR versions of HELIFLEX® coaxial cables contribute to low system noise.
- Outstanding Intermodulation Performance**
HELIFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, HELIFLEX® cable provides safe long term operating life at high transmit power levels.
- Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical Features

APPLICATIONS

Applications	Wireless Communication	TV & Radio	HF Defense	Mobile Radio	Cable Solutions
--------------	------------------------	------------	------------	--------------	-----------------

STRUCTURE

Cable Type	HCA
Size	7/8"
Jacket Option	Indoor
Inner Conductor Material	Copper Tube
Dielectric Material	Helical Polyethylene Spacer
Outer Conductor Material	Corrugated Copper
Jacket Material	Black Polyethylene, Metalhydroxite Filling

**HCA78-50JFN**

7/8" HELIFLEX® Air-Dielectric Coaxial Cable, flame retardant/ halogen free jacket

MECHANICAL SPECIFICATIONS

Inner Conductor Diameter	9mm (0.35in)
Dielectric Diameter	20.2mm (0.79in)
Outer Conductor Diameter	25.5mm (1in)
Jacket Diameter	28mm (1.103in)
Cable Weight	0.68kg/m (0.46lb/ft)
Min Bending Radius, Single Bend	100mm (4in)
Min. Bending Radius, Repeated Bends	250mm (10in)
Bending Moment	27 Nm (20 lbf*ft)
Tensile Strength	1,600N (360lb)
Air Volume	0.34l/m (0.0037ft³/ft)
Recommended / Maximum Clamp Spacing	0.5 / 0.9 m (1.8 / 3) ft

ELECTRICAL SPECIFICATIONS

Impedance	50 +/- 0.5 Ω
Max. Operating Frequency	3 GHz
Velocity	93 %
Capacitance	71pF/m (21.6pF/ft)
Inductance	0.178 μ H/m (0.054 μ H/ft)
Peak Power Rating	73 kW
RF Peak Voltage	2,700 V
Jacket Spark	8,000 V RMS
DC-Resistance Inner Conductor	1.1 Ω /km (0.34 Ω /kft)
DC-Resistance Outer Conductor	0.88 Ω /km (0.27 Ω /kft)
Return Loss (VSWR) Performance	Standard
Min. Return Loss (Max. VSWR)	Typical 20.8dBdB (1.2 VSWR or better within the operation bands of most global frequency ranges. Premium also available. Contact factory for options in your specific frequency band.VSWR)

TESTING AND ENVIRONMENTAL

Fire Performance	Flame Retardant, Halogen Free, Low Smoke
Compliance	RoHS 2011/65/EU China RoHS SJ/T 11364-2006 IEC 60754-1/-2 Halogen Acid Gases REACH (EC 1907/2006) IEC 60332-1 Single-Cable Flame Test IEC 61034-1, -2 Smoke Density Measurement EN 50575:2014 + A1:2016 Construction Products Regulation
Phase Stabilized	Phase stabilized and phase matched cables and assemblies are available upon request.
Installation Temperature	-40°C to 60°C (-40°F to 140°F)
Storage Temperature	-70°C to 85°C (-94°F to 185°F)
Operation Temperature	-50°C to 85°C (-58°F to 185°F)

**HCA78-50JFN**

7/8" HELIFLEX® Air-Dielectric Coaxial Cable, flame retardant/ halogen free jacket

ATTENUATION AND POWER RATING

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
0.5	0.081	0.025	73
1	0.115	0.035	73
1.5	0.141	0.043	70.9
2	0.163	0.05	61.4
10	0.366	0.112	27.3
20	0.52	0.158	19.2
30	0.638	0.194	15.7
50	0.827	0.252	12.1
88	1.1	0.337	9.11
100	1.18	0.359	8.49
108	1.23	0.374	8.15
150	1.45	0.443	6.92
174	1.57	0.478	6.39
200	1.69	0.514	5.94
300	2.08	0.634	4.84
400	2.42	0.738	4.17
450	2.57	0.785	3.93
500	2.72	0.83	3.71
512	2.76	0.84	3.66
600	3	0.914	3.37
700	3.25	0.992	3.12
800	3.49	1.07	2.91
824	3.55	1.08	2.86
894	3.71	1.13	2.74
900	3.72	1.13	2.74
925	3.78	1.15	2.69
960	3.85	1.17	2.65
1000	3.94	1.2	2.59
1250	4.45	1.36	2.3
1500	4.91	1.5	2.1
1700	5.26	1.6	1.97
1800	5.43	1.65	1.91
2000	5.75	1.75	1.81
2200	6.07	1.85	1.72
2300	6.22	1.9	1.68
3000	7.22	2.2	1.47
Note	Standard Conditions: For attenuation: VSWR 1.0, cable temperature 20°C (68°F). For average power: VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 115°C (239°F). No solar loading.		

External Document Links

Notes