




LCF12-50JL
1/2" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable



CELLFLEX® Lite 1/2" low loss cable

Features / Benefits

- **Ultra Low Attenuation**
The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- **Complete Shielding**
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical Features

STRUCTURE

Cable Type	LCF
Size	1/2"
Jacket Option	Outdoor
Inner Conductor Material	Copper-Clad Aluminium Wire
Dielectric Material	Foam Polyethylen
Outer Conductor Material	Corrugated Aluminium
Jacket Material	Black Polyethylen



LCF12-50JL
1/2" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable

MECHANICAL SPECIFICATION

Inner Conductor Diameter	4.8mm (0.189in)
Dielectric Diameter	11.2mm (0.44in)
Outer Conductor Diameter	13.8mm (0.54in)
Jacket Diameter	15.9mm (0.62in)
Cable Weight	0.166kg/m (0.112lb/ft)
Min. Bending Radius, Single Bend	70mm (3in)
Min. Bending Radius, Repeated Bends	125mm (5in)
Bending Moment	6.5Nm (4.797ft-lbf)
Tensile Strength	800N (180lb)
Max. Pulling Length per Hoisting Grip	60m (2,362.205in)
Recommended Clamp Spacing	0.6m (1.969ft)

ELECTRICAL SPECIFICATION

Impedance	50 ±1 Ω
Max. Operating Frequency	8.8 GHz
Velocity	88 %
Capacitance	76pF/m (23.2pF/ft)
Inductance	0.19µH/m (0.058µH/ft)
Peak Power Rating	38 kW
RF Peak Voltage	1.95 kV
Jacket Spark	8 kV
DC-Resistance Inner Conductor	1.57Ω/km (0.479Ω/kft)
DC-Resistance Outer Conductor	2.4Ω/km (0.732Ω/kft)
Return Loss (VSWR) Performance	Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies.

**LCF12-50JL**

1/2" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable

TESTING AND ENVIRONMENTAL

Fire Performance	Halogen Free
Compliance	RoHS 2011/65/EU China RoHS SJ/T 11364-2006 REACH (EC 1907/2006) IEC 60754-1/-2 Halogen Acid Gases
Installation Temperature, Minimum	-40°C (-40°F)
Installation Temperature, Maximum	60°C (140°F)
Storage Temperature, Minimum	-70°C (-94°F)
Storage Temperature, Maximum	85°C (185°F)
Operation Temperature, Minimum	-40°C (-40°F)
Operation Temperature, Maximum	85°C (185°F)

ATTENUATION AND POWER RATING

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
88	2.22	0.676	4.01
100	2.37	0.722	3.76
150	2.91	0.888	3.06
200	3.38	1.03	2.63
450	5.13	1.57	1.73
700	6.47	1.97	1.38
800	6.94	2.12	1.28
894	7.36	2.24	1.21
900	7.39	2.25	1.2
960	7.64	2.33	1.16
1800	10.7	3.26	0.832
2000	11.3	3.45	0.788
2200	11.9	3.63	0.748
2400	12.5	3.81	0.712
2600	13.1	3.98	0.679
2700	13.3	4.06	0.669
3000	14.1	4.3	0.631
3500	15.4	4.69	0.578
4000	16.6	5.05	0.536
5000	18.8	5.72	0.473
6000	20.8	6.34	0.428
Note	Standard Conditions: For attenuation: VSWR 1.0, cable temperature 20°C (68°F). For average power: VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F). No solar loading.		