




LCF38-50J
3/8" CELLFLEX® Low-Loss Foam-Dielectric Coaxial Cable



CELLFLEX® 1/4" low loss cable

Features / Benefits

- **Ultra Low Attenuation**
The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- **Complete Shielding**
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

Technical Features

STRUCTURE

Cable Type	LCF
Size	3/8"
Jacket Option	Outdoor
Inner Conductor Material	Copper-Clad Aluminium Wire
Dielectric Material	Foam Polyethylen
Outer Conductor Material	Corrugated Copper
Jacket Material	Black Polyethylen

**LCF38-50J**

3/8" CELLFLEX® Low-Loss Foam-Dielectric Coaxial Cable

MECHANICAL SPECIFICATION

Inner Conductor Diameter	3.1mm (0.122in)
Dielectric Diameter	7.2mm (0.283in)
Outer Conductor Diameter	9.5mm (0.374in)
Jacket Diameter	11.2mm (0.441in)
Cable Weight	0.13kg/m (0.087lb/ft)
Min. Bending Radius, Single Bend	50mm (1.968in)
Min. Bending Radius, Repeated Bends	95mm (3.74in)
Tensile Strength	530N (119.149lb)
Max. Pulling Length per Hoisting Grip	60m (2,362.205in)
Recommended Clamp Spacing	0.5m (1.64ft)
Max. Clamp Spacing	1m (3.281ft)

ELECTRICAL SPECIFICATION

Impedance	50 $\pm$ 1.5 Ω
Max. Operating Frequency	13.5 GHz
Velocity	88 %
Capacitance	76pF/m (23.165pF/ft)
Peak Power Rating	15.4 kW
RF Peak Voltage	1.24 kV
Jacket Spark	5 kV
DC-Resistance Inner Conductor	3.8 Ω /km (1.158 Ω /kft)
DC-Resistance Outer Conductor	2.9 Ω /km (0.884 Ω /kft)
Return Loss (VSWR) Performance	Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies.

**LCF38-50J****3/8" CELLFLEX® Low-Loss Foam-Dielectric Coaxial Cable****TESTING AND ENVIRONMENTAL**

Fire Performance	Halogen Free
Compliance	RoHS 2011/65/EU China RoHS SJ/T 11364-2006 IEC 60754-1/-2 Halogen Acid Gases REACH (EC 1907/2006) IEC 60754-1/-2 Halogen Acid Gases
Phase Stabilized	Phase stabilized and phase matched cables are available upon request.
Installation Temperature, Minimum	-40°C (-40°F)
Installation Temperature, Maximum	60°C (140°F)
Storage Temperature, Minimum	-70°C (-94°F)
Storage Temperature, Maximum	85°C (185°F)
Operation Temperature, Minimum	-50°C (-58°F)
Operation Temperature, Maximum	85°C (185°F)

ATTENUATION AND POWER RATING

Frequency, MHz	dB per 100m	dB per 100ft	Power, kW
75	2.96	0.90	2.45
100	3.43	1.04	2.12
150	4.21	1.28	1.72
200	4.89	1.49	1.48
450	7.44	2.27	0.97
700	9.38	2.86	0.77
800	10.06	3.07	0.72
870	10.52	3.21	0.69
900	10.71	3.27	0.68
960	11.09	3.38	0.65
1800	15.54	4.74	0.47
2000	16.45	5.01	0.44
2200	17.33	5.28	0.42
2400	18.17	5.54	0.40
2600	18.99	5.79	0.38
2700	19.39	5.91	0.37
3000	20.55	6.26	0.35
3500	22.39	6.82	0.32
4000	24.12	7.35	0.30
5000	27.35	8.34	0.27
6000	30.34	9.25	0.24
Note	Standard Conditions: For attenuation: VSWR 1.0, cable temperature 20°C (68°F). For average power: VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F). No solar loading.		



LCF38-50J
3/8" CELLFLEX® Low-Loss Foam-Dielectric Coaxial Cable

NOTES

LCFXX-50JTC: TC cables (temperature cycled) are cables that are aged in order to reduce hysteresis effects. Available upon request.