




**LCF78-50JL**  
7/8" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable



CELLFLEX® Lite 7/8" low loss cable

**Features / Benefits**

- **Ultra Low Attenuation**  
The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- **Complete Shielding**  
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**  
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**  
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**  
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**  
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

**Technical Features**

**STRUCTURE**

|                          |                      |
|--------------------------|----------------------|
| Cable Type               | LCF                  |
| Size                     | 7/8"                 |
| Jacket Option            | Outdoor              |
| Inner Conductor Material | Copper Tube          |
| Dielectric Material      | Foam Polyethylen     |
| Outer Conductor Material | Corrugated Aluminium |
| Jacket Material          | Black Polyethylen    |



**LCF78-50JL**  
7/8" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable

MECHANICAL SPECIFICATION

|                                       |                       |
|---------------------------------------|-----------------------|
| Inner Conductor Diameter              | 9.32mm (0.367in)      |
| Dielectric Diameter                   | 21.5mm (0.846in)      |
| Outer Conductor Diameter              | 25.2mm (0.992in)      |
| Jacket Diameter                       | 27.8mm (1.094in)      |
| Cable Weight                          | 0.32kg/m (0.215lb/ft) |
| Min. Bending Radius, Single Bend      | 120mm (5in)           |
| Min. Bending Radius, Repeated Bends   | 250mm (10in)          |
| Bending Moment                        | 13Nm (9.594ft-lbf)    |
| Tensile Strength                      | 1,440N (324lb)        |
| Max. Pulling Length per Hoisting Grip | 60m (2,362.205in)     |
| Recommended Clamp Spacing             | 0.8m (2.625ft)        |
| Max. Clamp Spacing                    | 1m (3.281ft)          |

ELECTRICAL SPECIFICATION

|                                |                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------|
| Impedance                      | 50 ±1 Ω                                                                         |
| Max. Operating Frequency       | 5 GHz                                                                           |
| Velocity                       | 90 %                                                                            |
| Capacitance                    | 75pF/m (22.9pF/ft)                                                              |
| Peak Power Rating              | 85 kW                                                                           |
| RF Peak Voltage                | 2.92 kV                                                                         |
| Jacket Spark                   | 5 kV                                                                            |
| DC-Resistance Inner Conductor  | 2.04Ω/km (0.622Ω/kft)                                                           |
| DC-Resistance Outer Conductor  | 1.42Ω/km (0.433Ω/kft)                                                           |
| Return Loss (VSWR) Performance | Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies. |

**LCF78-50JL**

7/8" CELLFLEX® Lite Low-Loss Foam-Dielectric Coaxial Cable

**TESTING AND ENVIRONMENTAL**

|                                   |                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------|
| Fire Performance                  | Halogen Free                                                                                               |
| Compliance                        | RoHS 2011/65/EU<br>China RoHS SJ/T 11364-2006<br>REACH (EC 1907/2006)<br>IEC 60754-1/-2 Halogen Acid Gases |
| Installation Temperature, Minimum | -40°C (-40°F)                                                                                              |
| Installation Temperature, Maximum | 60°C (140°F)                                                                                               |
| Storage Temperature, Minimum      | -70°C (-94°F)                                                                                              |
| Storage Temperature, Maximum      | 85°C (185°F)                                                                                               |
| Operation Temperature, Minimum    | -50°C (-58°F)                                                                                              |
| Operation Temperature, Maximum    | 85°C (185°F)                                                                                               |

**ATTENUATION AND POWER RATING**

| Frequency, MHz | dB per 100m                                                                                                                                                                                                         | dB per 100ft | Power, kW |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|
| 88             | 1.18                                                                                                                                                                                                                | 0.36         | 8.98      |
| 100            | 1.26                                                                                                                                                                                                                | 0.384        | 8.41      |
| 150            | 1.55                                                                                                                                                                                                                | 0.473        | 6.84      |
| 200            | 1.8                                                                                                                                                                                                                 | 0.549        | 5.89      |
| 450            | 2.74                                                                                                                                                                                                                | 0.837        | 3.87      |
| 700            | 3.46                                                                                                                                                                                                                | 1.06         | 3.06      |
| 800            | 3.72                                                                                                                                                                                                                | 1.13         | 2.85      |
| 894            | 3.95                                                                                                                                                                                                                | 1.2          | 2.68      |
| 900            | 3.96                                                                                                                                                                                                                | 1.21         | 2.68      |
| 960            | 4.1                                                                                                                                                                                                                 | 1.25         | 2.59      |
| 1800           | 5.76                                                                                                                                                                                                                | 1.76         | 1.84      |
| 2000           | 6.1                                                                                                                                                                                                                 | 1.86         | 1.74      |
| 2200           | 6.43                                                                                                                                                                                                                | 1.96         | 1.65      |
| 2400           | 6.75                                                                                                                                                                                                                | 2.06         | 1.57      |
| 2600           | 7.05                                                                                                                                                                                                                | 2.15         | 1.5       |
| 2700           | 7.2                                                                                                                                                                                                                 | 2.2          | 1.47      |
| 3000           | 7.64                                                                                                                                                                                                                | 2.33         | 1.39      |
| 3500           | 8.33                                                                                                                                                                                                                | 2.54         | 1.27      |
| 4000           | 8.98                                                                                                                                                                                                                | 2.74         | 1.18      |
| 5000           | 10.2                                                                                                                                                                                                                | 3.11         | 1.04      |
| Note           | Standard Conditions:<br>For attenuation: VSWR 1.0, cable temperature 20°C (68°F).<br>For average power: VSWR 1.0, ambient temperature 40°C (104°F), inner conductor temperature 100°C (212°F).<br>No solar loading. |              |           |