



**LCFS114-50JFNA**

1-1/4" CELLFLEX® Low-Loss Foam-Dielectric Coaxial Cable, Flame Retardant Jacket



CELLFLEX® 1-1/4" low loss cable

**Features / Benefits**

- **Ultra Low Attenuation**  
The reduced attenuation of CELLFLEX® coaxial cable results in extremely efficient signal transfer in your RF system, especially at high frequencies.
- **Complete Shielding**  
The solid outer conductor of CELLFLEX® coaxial cable creates a continuous RFI/EMI shield that minimizes system interference.
- **Low VSWR**  
Special low VSWR versions of CELLFLEX® coaxial cables contribute to low system noise.
- **Outstanding Intermodulation Performance**  
CELLFLEX® coaxial cable's solid inner and outer conductors virtually eliminate intermods. Intermodulation performance is also confirmed with state-of-the-art equipment at the RFS factory.
- **High Power Rating**  
Due to their low attenuation, outstanding heat transfer properties and temperature stabilized dielectric materials, CELLFLEX® cable provides safe long term operating life at high transmit power levels.
- **Wide Range of Application**  
Typical areas of application are: feedlines for broadcast and terrestrial microwave antennas, wireless cellular, PCS and ESMR base stations, cabling of antenna arrays, and radio equipment interconnects.

**Technical Features**

**STRUCTURE**

|                          |                                           |
|--------------------------|-------------------------------------------|
| Cable Type               | LCF                                       |
| Size                     | 1-1/4"                                    |
| Jacket Option            | Indoor                                    |
| Inner Conductor Material | Corrugated Copper Tube                    |
| Dielectric Material      | Foam Polyethylen                          |
| Outer Conductor Material | Corrugated Copper                         |
| Jacket Material          | Black Polyethylen, Metalhydroxite Filling |



LCFS114-50JFNA

1-1/4" CELLFLEX® Low-Loss Foam-Dielectric Coaxial Cable, Flame Retardant Jacket

MECHANICAL SPECIFICATION

|                                       |                       |
|---------------------------------------|-----------------------|
| Inner Conductor Diameter              | 13.1mm (0.516in)      |
| Dielectric Diameter                   | 31.2mm (1.228in)      |
| Outer Conductor Diameter              | 35.9mm (1.413in)      |
| Jacket Diameter                       | 39mm (1.535in)        |
| Cable Weight                          | 0.96kg/m (0.645lb/ft) |
| Min. Bending Radius, Single Bend      | 200mm (7.874in)       |
| Min. Bending Radius, Repeated Bends   | 380mm (14.961in)      |
| Bending Moment                        | 43Nm (31.734ft-lbf)   |
| Tensile Strength                      | 2,490N (559.774lb)    |
| Max. Pulling Length per Hoisting Grip | 60m (2,362.205in)     |
| Recommended Clamp Spacing             | 1m (3.281ft)          |
| Max. Clamp Spacing                    | 0.2m (0.656ft)        |

ELECTRICAL SPECIFICATION

|                                |                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------|
| Impedance                      | 50 ±1 Ω                                                                         |
| Max. Operating Frequency       | 3.7 GHz                                                                         |
| Velocity                       | 89 %                                                                            |
| Capacitance                    | 74pF/m (22.555pF/ft)                                                            |
| Peak Power Rating              | 176 kW                                                                          |
| RF Peak Voltage                | 4.2 kV                                                                          |
| Jacket Spark                   | 5 kV                                                                            |
| DC-Resistance Inner Conductor  | 0.83Ω/km (0.253Ω/kft)                                                           |
| DC-Resistance Outer Conductor  |                                                                                 |
| Return Loss (VSWR) Performance | Standard 20dB (1.222) / Premium 23/24dB (1.152/1.135) on specified frequencies. |

**LCFS114-50JFNA**

1-1/4" CELLFLEX® Low-Loss Foam-Dielectric Coaxial Cable, Flame Retardant Jacket

**TESTING AND ENVIRONMENTAL**

|                                   |                                                                                                                                                                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire Performance                  | Flame Retardant, Halogen Free, Low Smoke                                                                                                                                                                                                                   |
| Compliance                        | RoHS 2011/65/EU<br>China RoHS SJ/T 11364-2006<br>IEC 60754-1/-2 Halogen Acid Gases<br>REACH (EC 1907/2006)<br>IEC 60332-1 Single-Cable Flame Test<br>IEC 61034-1, -2 Smoke Density Measurement<br>EN 50575:2014 + A1:2016 Construction Products Regulation |
| Phase Stabilized                  | Phase stabilized and phase matched cables are available upon request.                                                                                                                                                                                      |
| Installation Temperature, Minimum | -25°C (-13°F)                                                                                                                                                                                                                                              |
| Installation Temperature, Maximum | 60°C (140°F)                                                                                                                                                                                                                                               |
| Storage Temperature, Minimum      | -70°C (-94°F)                                                                                                                                                                                                                                              |
| Storage Temperature, Maximum      | 85°C (185°F)                                                                                                                                                                                                                                               |
| Operation Temperature, Minimum    | -50°C (-58°F)                                                                                                                                                                                                                                              |
| Operation Temperature, Maximum    | 85°C (185°F)                                                                                                                                                                                                                                               |

**ATTENUATION AND POWER RATING**

| Frequency, MHz | dB per 100m                                    | dB per 100ft | Power, kW |
|----------------|------------------------------------------------|--------------|-----------|
| 75             | 0.70                                           | 0.21         | 15.62     |
| 100            | 0.82                                           | 0.25         | 13.46     |
| 150            | 1.01                                           | 0.31         | 10.90     |
| 200            | 1.17                                           | 0.36         | 9.37      |
| 450            | 1.81                                           | 0.55         | 6.09      |
| 700            | 2.29                                           | 0.70         | 4.80      |
| 800            | 2.47                                           | 0.75         | 4.46      |
| 870            | 2.58                                           | 0.79         | 4.26      |
| 900            | 2.63                                           | 0.80         | 4.18      |
| 960            | 2.73                                           | 0.83         | 4.03      |
| 1800           | 3.88                                           | 1.18         | 2.83      |
| 2000           | 4.12                                           | 1.26         | 2.67      |
| 2200           | 4.35                                           | 1.33         | 2.53      |
| 2400           | 4.58                                           | 1.39         | 2.40      |
| 2600           | 4.80                                           | 1.46         | 2.29      |
| 2700           | 4.90                                           | 1.49         | 2.24      |
| 3000           | 5.21                                           | 1.59         | 2.11      |
| 3500           | 5.71                                           | 1.74         | 1.93      |
| 3700           | 5.90                                           | 1.80         |           |
| Note           | @ 20°C (68°F) and power rating @ 40°C (104°F). |              |           |

**NOTES**

LCFXX-50JTC: TC cables (temperature cycled) are cables that are aged in order to reduce hysteresis effects. Available upon request.