




**MBH158-2-F**

Double Multi-block hanger one layer, with angle member adapter



Double Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds two runs of coax, allowing a compact bundle of up to 6x runs to be supported by stacking three blocks.

**Technical Features**

**GENERAL SPECIFICATIONS**

|              |                    |
|--------------|--------------------|
| Product Type | Hanger             |
| Hanger Type  | Single Multi-block |
| Color        | Black              |

**MECHANICAL SPECIFICATIONS**

|                                             |                                                                                                                                |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Cable Size                                  | 1 5/8                                                                                                                          |
| Number of Cable / Waveguide Runs            | 2 per layer, 1 layer, 2 run                                                                                                    |
| Configuration                               | incl. Angle member adapter                                                                                                     |
| Material                                    | Metal parts:<br>-Connecting devices:Stainless steel<br>-Angle member adapter: Stainless steel<br>-Plastic parts: Polypropylene |
| Length                                      | 190mm (7.48in)                                                                                                                 |
| Height                                      | 135mm (5.31in)                                                                                                                 |
| Width                                       | 55mm (2.17in)                                                                                                                  |
| Angle member adapter clamping range mm (in) | 4 / 24 (0.157 / 0.945 )                                                                                                        |
| Angle member adpter threads                 | 2x M8                                                                                                                          |
| Recommended / Maximum Clamp Spacing         | 1 / 1.2 (3.25 / 4)                                                                                                             |

**TESTING AND ENVIRONMENTAL**

|                       |                                |
|-----------------------|--------------------------------|
| Operation Temperature | -50°C to 85°C (-58°F to 185°F) |
| Storage Temperature   | -50°C to 85°C (-58°F to 185°F) |



**Related Documents**



Installation Instruction  
Installation Instructions