


**MBHS114-3-F**

Single Multi-block hanger, with angle member adapter



Single Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds one run of coax, allowing a compact bundle of up to 3x runs to be supported by stacking three blocks.

Features / Benefits

- Single Multi Blocks are manufactured of polypropylene providing thermal, chemical and UV resistance in all environments.
- They come including angle member adapter and necessary hardware.
- The angle member adapter fastens the clamp to the tower without drilling.
- The angle member adapter includes a tower member set screw.
- The hanger mounting rod may be located in either of two mounting holes, depending on orientation of the fixing member.
- Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.

Technical Features**GENERAL SPECIFICATIONS**

Product Type	Hanger
Hanger Type	Single Multi-block
Cable Type	Coaxial Foam Dielectric, Hybrid
Color	Black

MECHANICAL SPECIFICATIONS

Cable Size	1-1/4
Number of Cable / Waveguide Runs	1 per layer, 3 layers, 3 runs
Configuration	incl. Angle member adapter
Material	Metal part: Stainless steel Plastic parts: Polypropylene
Length	290mm (11.4) see picture belowin)
Height	80mm (3.15) see picture belowin)
Width	50mm (1.96) see picture belowin)
Angle member adapter clamping range mm (in)	4 / 24 (0.157 / 0.945)
Angle member adppter threads	2x M8
Recommended / Maximum Clamp Spacing	0.9 / 1.2 (2.95 / 4)

TESTING AND ENVIRONMENTAL

Operation Temperature	-50°C to 85°C (-58°F to 185°F)
Storage Temperature	-50°C to 85°C (-58°F to 185°F)

**Related Documents**



MBHS114-3-F

Single Multi-block hanger, with angle member adapter



Installation Instruction
Installation Instructions