


**MBHS78-1-F**

Single Multi-block hanger one layer, with angle member adapter



Single Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds one run of coax, allowing a compact bundle of up to 3x runs to be supported by stacking three blocks.

**Features / Benefits**

- Single Multi Blocks are manufactured of polypropylene providing thermal, chemical and UV resistance in all environments.
- They come including angle member adapter and necessary hardware.
- The angle member adapter fastens the clamp to the tower without drilling.
- The angle member adapter includes a tower member set screw.
- The hanger mounting rod may be located in either of two mounting holes, depending on orientation of the fixing member.
- Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.

**Technical Features****GENERAL SPECIFICATIONS**

|              |                                 |
|--------------|---------------------------------|
| Product Type | Hanger                          |
| Hanger Type  | Single Multi-block              |
| Cable Type   | Coaxial Foam Dielectric, Hybrid |
| Color        | Black                           |

**MECHANICAL SPECIFICATIONS**

|                                             |                                                             |
|---------------------------------------------|-------------------------------------------------------------|
| Cable Size                                  | 7/8                                                         |
| Number of Cable / Waveguide Runs            | 1 per layer, 1 layer, 1 run                                 |
| Configuration                               | incl. Angle member adapter                                  |
| Material                                    | Metal part: Stainless steel<br>Plastic parts: Polypropylene |
| Length                                      | 150mm (5.90) see picture belowin)                           |
| Height                                      | 70mm (2.73) see picture belowin)                            |
| Width                                       | 50mm (1.96) see picture belowin)                            |
| Angle member adapter clamping range mm (in) | 4 / 24 (0.157 / 0.945 )                                     |
| Angle member adppter threads                | 2x M8                                                       |
| Recommended / Maximum Clamp Spacing         | 0.8 / 1 (2.75 / 3.25)                                       |

**TESTING AND ENVIRONMENTAL**

|                       |                                |
|-----------------------|--------------------------------|
| Operation Temperature | -50°C to 85°C (-58°F to 185°F) |
| Storage Temperature   | -50°C to 85°C (-58°F to 185°F) |

**Related Documents**



**MBHS78-1-F**

Single Multi-block hanger one layer, with angle member adapter



**Installation Instruction**  
Installation Instructions