

**NF-SCF38-D01**

N Female Connector for 3/8" Coaxial Cable, OMNI FIT™ Premium,
Straight, threaded gasket and 360° compression sealing



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment.

All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The N connector meets all technical requirements and covers high frequencies as well as legacy applications.

Sealing against outer conductor and jacket by means of threaded gasket and 360° compression fit.

Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.;

Features / Benefits

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Unique NiTin plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical Features

STRUCTURE

Cable Type	SCF
Cable Size	3/8"
Model Series	D01 Premium Series
Connector Interface Size	N
Connector Interface Gender	Female

MECHANICAL SPECIFICATIONS

Connector Length	45.2mm (1.78in)
Connector Outer Diameter	20mm (0.79in)

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 Ω	
Connector Frequency Range	DC - 3.7 GHz GHz	
PIM Ratio (2 x 20 W Carrier)	-156 dBc	
PIM ratio Typical (2 x 20 W Carrier)	-162 dBc	
Frequency Range	VSWR	Return Loss
0 < f ≤ 1.0 GHz	1.02	40
1.0 < f ≤ 2.7 GHz	1.03	36.6
2.7 < f ≤ 3.7 GHz	1.06	30.7



NF-SCF38-D01

N Female Connector for 3/8" Coaxial Cable, OMNI FIT™ Premium,
Straight, threaded gasket and 360° compression sealing

TESTING AND ENVIRONMENTAL

Ingress Protection (IP) Rating	IP68
--------------------------------	------

ACCESSORIES

Wrench Size Connector Front Part	20mm (13/16in)
Wrench Size Connector Rear Part	20mm (13/16in)



Related Documents



Installation Instruction

Installation Instructions