


**NM-LCF78-D01****N Male Connector for 7/8" Coaxial Cable, OMNI FIT™ Premium,
Straight, O-Ring and compression sealing**

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The N connector meets all technical requirements and covers high frequencies as well as legacy applications. Sealing against outer conductor and jacket by means of O-Ring and 360° compression fit. Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.

Features / Benefits

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Unique NiTin plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis

Technical Features**STRUCTURE**

Cable Type	LCF
Cable Size	7/8"
Model Series	D01 Premium Series
Connector Interface Size	N
Connector Interface Gender	Male

MECHANICAL SPECIFICATIONS

Connector Length	73.65mm (2.9in)
Connector Outer Diameter	40mm (1.57in)

ELECTRICAL SPECIFICATIONS

Nominal Impedance	50 Ω	
Connector Frequency Range	DC - 3.7 GHz GHz	
PIM Ratio (2 x 20 W Carrier)	-156 dBc	
PIM ratio Typical (2 x 20 W Carrier)	-162 dBc	
Frequency Range	VSWR	Return Loss
0 < f ≤ 1.0 GHz	1.02	40
1.0 < f ≤ 2.7 GHz	1.03	36.6
2.7 < f ≤ 3.7 GHz	1.06	30.7



NM-LCF78-D01

N Male Connector for 7/8" Coaxial Cable, OMNI FIT™ Premium,
Straight, O-Ring and compression sealing

TESTING AND ENVIRONMENTAL

Ingress Protection (IP) Rating	IP68
--------------------------------	------

ACCESSORIES

Wrench Size Connector Front Part	36mm (1-7/16in)
Wrench Size Connector Rear Part	36mm (1-7/16in)
Trimming Tool	TRIM-78-L TRIM-SET-L78-D01 TRIM-LCF78-D01-A



Related Documents

 Installation Instruction **-LCF78-D01
Installation Instructions