



PPIF-0Z12SL-MLAP-YC

Interface module, 2 x MTP12(m) to 24 x LC/APC, SMF



The HYBRIFLEX™ Interface module to enable backbone cables terminated with MTP12 (female) connectors to be connected to 24 single fiber LC/APC connections. Optimised for RoF (Radio over Fibre) applications, for use within the RFS "Plug and Play" RoF solution. These modules fit inside the 19" rack mounted patch panel chassis (PPIF-0Z48Z-1U-YC).

Features / Benefits

- High precision MTP and LC/APC fiber connectors provide low insertion loss, high return loss and excellent stability and durability
- All connectors are terminated and fully tested in controlled conditions to ensure optimum performance and reliability
- "Plug and Play" solution simplifies network design, minimizes installation/testing time and the necessary on site skills

Technical Features

MECHANICAL SPECIFICATIONS

Material of Housing	Electrostatic epoxy powder coated steel
Dimensions (LxWxD)	80 x 93 x 34.8 (3.15 x 3.66 x 13.7)
Mounting	Patch Panel Chassis Mount
Connector Interface 1	2 x MTP12
Connector Interface 2	12 x LC/APC duplex

ENVIRONMENTAL

Storage Humidity	≤ 90% (+30 °C)
Operating Humidity	≤ 93%(+40°C)

CABLES SUPPORTED

Supported F/O Connections	24 Fiber
---------------------------	----------