




PW-S-04U3-J22

Power Connect cable 4 mm² for connection of one RRU



RFS' HYBRIFLEX™ cabling solution for Remote Radio Unit (RRU) combines optical fiber and DC power in a single lightweight aluminum corrugated cable, making it the world's most innovative solution for RRU deployments. It was developed to reduce installation complexity and cost at Cellular sites.

HYBRIFLEX™ cabling solutions allows mobile operators deploying RRU architecture to standardized installation process and eliminates the need for and the cost of cable grounding.

The **HYBRIFLEX™** Power Connect cable **PW-S-04U3-J22** consists of three unshielded pairs

DC wires protected by a corrugated Aluminum armor.

Features / Benefits

- UV resistant jacket
- Comply with IEC 60228
- Flexible

Technical Features

STRUCTURE

Cable Type	HYBRIFLEX™ Power Cable
Number of Copper Wire Pairs	3
Jacket Material	UV stable black PE

MECHANICAL SPECIFICATIONS

Outer Diameter Nominal	28.5mm (1.102in)
Cable Weight	0.741kg/m (0.498lb/ft)
Minimum Single Bending Radius	160mm (6.3in)
Minimum Multi Bending Radius	220mm (8.66in)
Recommended / Maximum Clamp Spacing	0.8 / 1 (2 / 3.25)

**PW-S-04U3-J22**Power Connect cable 4 mm² for connection of one RRU**DC POWER CABLE SPECIFICATIONS**

Maximum DC-Resistance Power Cable	4.95Ω/km (1.51Ω/kft)
Jacket Material	UV stable black PE
Cross Section of Copper Wire Nicolas	4mm ² (12AWG)
Shielding	No separate shielding per DC pair
Individual Copper Wire Jacket Material	UV stable black and blue PE
Individual Copper Wire Jacket Thickness	0.65mm (0.025in)
Individual Copper Wire Single Bending Radius	53mm (2.1in)
Individual Copper Wire Diameter	4.4mm (1.73in)
DC Cable Jacket	UV stable black MDPE

ARMOR SPECIFICATIONS

Armor Type	Corrugated aluminium armor
------------	----------------------------

ENVIRONMENTAL

Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Operation Temperature	-40°C to 85°C (-40°F to 185°F)
Installation Temperature	-20°C to 50°C (-4°F to 122°F)

TESTING

Fire Performance	PE
Standards (Meets or Exceeds)	IEC 60228