

**PW-S-06U3-J22**Power Connect cable 6mm² for connection of three RRU

RFS' HYBRIFLEX™ cabling solution for Remote Radio Unit (RRU) combines optical fiber and DC power in a single lightweight aluminum corrugated cable, making it the world's most innovative solution for RRU deployments. It was developed to reduce installation complexity and cost at Cellular sites.

HYBRIFLEX™ cabling solutions allows mobile operators deploying RRU architecture to standardized installation process and eliminates the need for and the cost of cable grounding.

The **HYBRIFLEX™** Power Connect cable **PW-S-06U3-J22** is part of a site installation kit. It consists of three unshielded pairs..

Features / Benefits

- UV resistant jacket
- Comply with IEC 60228
- Flexible

Technical Features

STRUCTURE

Cable Type	HYBRIFLEX™ Power Cable
Number of Copper Wire Pairs	3

MECHANICAL SPECIFICATIONS

Outer Diameter Nominal	31mm (1.22in)
Minimum Single Bending Radius	120mm (4.724in)
Minimum Multi Bending Radius	254mm (10in)
Recommended / Maximum Clamp Spacing	0.6 / 1 (2 / 3.25)

DC POWER CABLE SPECIFICATIONS

Maximum DC-Resistance Power Cable	3.3Ω/km (1Ω/kft)
Cross Section of Copper Wire Nicolas	6mm ² (10AWG)
Shielding	No separate shielding per DC pair
Individual Copper Wire Jacket Material	UV stable black PE Blue and Black
Individual Copper Wire Jacket Thickness	0.65mm (0.025in)
Individual Copper Wire Single Bending Radius	53mm (2.1in)
Individual Copper Wire Diameter	4.4mm (0.173in)



PW-S-06U3-J22

Power Connect cable 6mm² for connection of three RRU

ENVIRONMENTAL

Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Operation Temperature	-40°C to 85°C (-40°F to 185°F)
Installation Temperature	-20°C to 50°C (-4°F to 122°F)