




**RLKW78-50JFNA**  
7/8" RADIAFLEX® RLKW Cable, A-series



- RADIAFLEX® functions as a distributed antenna to provide communications in tunnels, mines and large building complexes and is the solution for any application in confined areas.
- Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment. Conversely, a signal transmitted near the cable will couple into the slots and be carried along the cable length.
- RADIAFLEX® is used for both one-way and two-way communication systems and because of its broadband capability, a single radiating cable can handle multiple communication systems simultaneously.
- This RADIAFLEX® radiating cable utilize a low-loss cellular polyethylene foam dielectric and a smooth copper outer conductor which offers a superior electrical performance together with good bending properties.

**Features / Benefits**

- Wideband from 30 MHz to 1950 MHz
- For applications in tunnels and buildings
- Low coupling loss variationsv

**Technical Features**

**STRUCTURE**

|                              |                                                                              |
|------------------------------|------------------------------------------------------------------------------|
| Cable Type                   | RLKW                                                                         |
| Size                         | 7/8                                                                          |
| Inner Conductor Material     | Copper Tube                                                                  |
| Outer Conductor Material     | Overlapping Copper Foil                                                      |
| Jacket                       | JFN                                                                          |
| Jacket Description           | Halogen free, non corrosive, flame and fire retardant, low smoke, polyolefin |
| Slot Design                  | Groups of vertical slots at short intervals                                  |
| Indication of Slot Alignment | Bulge atop slots                                                             |

**MECHANICAL SPECIFICATION**

|                                     |                      |
|-------------------------------------|----------------------|
| Diameter Inner Conductor            | 9.3mm (0.37in)       |
| Diameter Outer Conductor            | 23.8mm (0.94in)      |
| Minimum Bending Radius              | 350mm (13.8in)       |
| Cable Weight                        | 0.55kg/m (0.37lb/ft) |
| Tensile Force                       | 2,300N (507lb)       |
| Recommended / Maximum Clamp Spacing | 0.9m (3ft)           |
| Minimum Distance to Wall            | 80mm (3.15in)        |

**RLKW78-50JFNA**

7/8" RADIAFLEX® RLKW Cable, A-series

**ELECTRICAL SPECIFICATION**

|                               |                                                                                      |     |           |
|-------------------------------|--------------------------------------------------------------------------------------|-----|-----------|
| Impedance                     | 50 +/- 2 $\Omega$                                                                    |     |           |
| Max. Operating Frequency      | 1,950 MHz                                                                            |     |           |
| Velocity                      | 89 %                                                                                 |     |           |
| Capacitance                   | 75pF/m (22.9pF/ft)                                                                   |     |           |
| Inductance                    | 0.188 $\mu$ H/m (0.057 $\mu$ H/ft)                                                   |     |           |
| DC-resistance inner conductor | 1.74 $\Omega$ /km (0.53 $\Omega$ /kft)                                               |     |           |
| DC-resistance outer conductor | 2.52 $\Omega$ /km (0.77 $\Omega$ /kft)                                               |     |           |
| Stop bands                    | 115-135, 235-255, 360-375, 475-505, 600-630, 720-750, 970-1075, 1340-1460, 1590-1700 |     |           |
| Frequency Selection           | 600                                                                                  | 900 | 1800/1900 |

**TESTING AND ENVIRONMENTAL**

|                          |                                                                                                                                                                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operation Temperature    | -40 - 85 °C (-40 - 185°F)                                                                                                                                                                                                                |
| Installation Temperature | -25 - 60 °C (-13 - 140°F)                                                                                                                                                                                                                |
| Storage Temperature      | -70 - 85 °C (-94 - 185°F)                                                                                                                                                                                                                |
| Compliance               | Test methods for fire behaviour of cable :<br>IEC 60754-1/-2 smoke emission: halogen free, non corrosive<br>IEC 61034 low smoke<br>IEC 60332-1 flame retardant<br>IEC 60332-3-24 fire retardant<br>UL1666, ASTM E 662, NES711 and NES713 |

**ATTENUATION AND COUPLING LOSS**

| Frequency, MHz | Longitudinal Loss, dB/100 m<br>(dB/100 ft) | Coupling Loss 50%, dB | Coupling Loss 95%, dB |
|----------------|--------------------------------------------|-----------------------|-----------------------|
| 75             | 1,05 (0,32)                                | 48 (52)               | 59 (63)               |
| 150            | 1,52 (0,46)                                | 57 (60)               | 66 (68)               |
| 380            | 2,56 (0,78)                                | 58 (61)               | 61 (65)               |
| 400            | 2,65 (0,81)                                | 58 (61)               | 61 (65)               |
| 450            | 2,88 (0,88)                                | 58 (61)               | 61 (65)               |
| 800            | 4,44 (1,35)                                | 60 (61)               | 62 (65)               |
| 870            | 5,14 (1,57)                                | 56 (58)               | 62 (64)               |
| 900            | 5,12 (1,56)                                | 56 (58)               | 64 (66)               |
| 960            | 5,47 (1,67)                                | 56 (58)               | 62 (64)               |
| 1800           | 13,32 (4,06)                               | 50 (52)               | 60 (63)               |
| 1900           | 14,62 (4,46)                               | 50 (52)               | 59 (63)               |

@ 20°C (68°F)

**NOTES**

- Coupling loss as well as longitudinal attenuation of RADIAFLEX® cables are measured by the free space method according to IEC 61196-4.
- Coupling loss values are measured with a radial (below 125 MHz and above 800 MHz) or parallel (125-800MHz) orientated dipole antenna.
- The coupling loss values given in brackets are average values of all three spatial orientations (radial, parallel and orthogonal) of dipole antenna.
- Coupling loss values are given with a tolerance of +5 dB and longitudinal loss values with a tolerance of +5%. Note: Measured values below nominal are better. They are not limited by any tolerance-range.



**RLKW78-50JFNA**

7/8" RADIAFLEX® RLKW Cable, A-series

- In case of a conflict of operational and stop band, please contact RFS for further assistance.
  - As with any radiating cable, the performance in building or tunnel environments may deviate from figures based on free space method.
- ;