



TF260-BW1-S-090M
TwistFlex PBR/UBR260, 0.9m



Twistable and flexible rectangular waveguide R260, with PBR/UBR 260 flanges. Length = 0.9m, core with environmental impact resistant molded rubber jacket. Hardware and gasket (for PDR/PBR flanges) included.

Features / Benefits

Waveguide installation

- The flexible and twistable rectangular waveguide component eliminates installation difficulties
- It isolates vibration
- It provides simple aid to positioning of antennas

Technical Features

STRUCTURE

Type of Rectangular Waveguide Component	TwistFlex
Waveguide Size IEC (EIA)	R260 (WR34)
Flange A	PBR260
Flange B	UBR260
Flange Finish	Brass un-plated
Package Quantity	1

ELECTRICAL SPECIFICATIONS

Frequency Range	21.7 - 33 GHz
Minimum Return Loss (max. VSWR)	20.1dB (1.22VSWR)
Attenuation	1.35 dB
Power rating	100 W

MECHANICAL SPECIFICATIONS

Maximum Twist	360°/m (110°/ft)
Minimum Bending Radius E-Plane	35mm (1.4in)
Minimum Bending Radius H-Plane	64mm (2.5in)
Length	900mm (35.4in)
Jacket Diameter	16 mm
Weight	0.25kg (0.55lb)

MATERIAL

Material	Core: Brass silver plated Jacket: Rubber Silicone Flange: Brass
Color	Black



TF260-BW1-S-090M

TwistFlex PBR/UBR260, 0.9m

External Document Links

Notes

Related Documents



AN 030707-8 Application note for RFS Twistflex
External Datasheet