




WOIF-0ZXXSS-APMW-YC

Optical Fiber Wall Outlet Box, surface mount including 2 or 4 x SC/APC adapters & pigtails



Optical fiber wall outlet for local termination of up to four optical fibers.

The unit includes fiber management and splice protection together with up to four SC/APC adapters and pigtails.

Features / Benefits

- Individual shutters provide dust protection for unused ports
- Full fiber management ensures optimum optical performance
- Splice protectors included
- Optional power connector included
- DIN 35 mountable

Technical Features

MECHANICAL SPECIFICATIONS

Material	ABS or PC+ABS
Dimensions (LxWxD)	80 x 80 x 31 (3.15 x 3.15 x 1.22)
Mounting	IP50 wall-mounted / recessed or DIN 35mm rail installation (IP40)

TESTING AND ENVIRONMENTAL

Storage Humidity	≤ 95% (+40 °C) -
------------------	------------------

CABLES SUPPORTED

Supported F/O Connections	SC/APC flangeless
Diameter of Jumper Cable	0.9mm (0.035in)

FAMILY INFORMATION

Column 1	Column 2	Column 3
	WOIF-0Z02SS-APMW-YC	WOIF-0Z04SS-APMW-YC
Quantity of Adapters	2	4
Quantity of Pigtails	2	4

