



WOIF-0ZXXSS-APPD-YC

Wall Outlet Box: configurable options: Compatible with Duplex LC/APC, Simplex SC/APC.

woif-0zxxss-apxx-yc
pic 1.jpg

RFS Optical fibre wall outlet is a fixed connection device, which is used to terminate the drop cable in the office area, residential area, business district, and is made up of bottom box and front cover. These optical fibre wall outlets are fire rated classified suitable for use in exposed and concealed type for installation. supplied for different applications requiring outlets, required to bring fiber to the desk or widely used in multi-floor and high tech in-building environment. According to the number of ports and ports type, these wall plate outlets are available with different ports and the adapters are preloaded into the wall plate outlets. As for multi-interface, RFS can customize the outlet according our customer's requirements. Fully complaint with RoHS providing protection for in and out fibres

Features / Benefits

- Flame Retardant Material - High-density ABS insulation materials, impact resistance,
- High temperature resistance, good gloss, safe to use.
- Atmospheric pressure: 70kPa 106kPa
- Cable types: drop cable, pigtail, outdoor cable(Φ8mm Φ10.5mm)
- Meet domestic standard Q/CT 2353-2011.

Wall Outlet, Indoor, Fiber Only, 0 DC,(Z)no Overvoltage protection, XX cores Fiber, Singlemode SC-APC, Pigtail, Adaptor, YC internal code

Technical Features

MECHANICAL SPECIFICATIONS

Dimensions (LxWxD)	86 x 86 x 26 (3.38 x 3.38 x 1.02)
--------------------	-----------------------------------

FAMILY INFORMATION

Column 1	Column 2	Column 3
	WOIF-0Z01SS-APPD-YC	WOIF-0Z02SS-APPD-YC
Quantity of Adapters	1	2
Quantity of Pigtails	1	2

